

Network Camera

TVT-B922POE

5.0MP IP Bullet Camera - 9 - 22mm Lens



- Power Over Ethernet
- 70 - 100m Infrared Range
- IP66 For New Zealand Conditions
- 2 Year Return to Base Warranty



HD CCTV


5 MP Network IR Water-proof Bullet Camera



Features

- 5MP (2592 × 1520) H.265 full real time coding
- Max. resolution: 2592 × 1520
- ICR auto switch, true day / night
- 70 ~ 100m IR night view distance
- 3D DNR, true WDR, HLC, BLC and defogging
- Motorized zoom lens
- ROI coding
- Support CVBS video output and two-way audio
- PoE power supply optional
- Support smart phone, iPad, remote monitoring
- P2P function optional
- Support three streams
- IP66 ingress protection
- Smart analytics (optional): object removal detection, abnormal video signal detection, line crossing detection, region intrusion detection, people intrusion detection, people counting detection, crowd density detection, etc.

Dimensions



Available Accessories



Specifications

Specifications	Model	TVT-B922POE
Camera		
Image Sensor		1 / 3 "CMOS
Image Size		2688 × 1520
Electronic Shutter		1 / 25 s ~ 1 / 100000 s
Iris Type		Fixed Iris
Min. Illumination		0.05 lux@F1.2, AGC ON; 0 lux with IR
Lens		9 ~ 22 mm @F1.4, angle of view: 29.5° ~ 16.2°
Lens Mount		Φ14
Day & Night		ICR
Wide Dynamic Range		120dB
BLC		Yes
HLC		Yes
Defogging		Yes
Digital NR		2D / 3D DNR
Angle Adjustment		Any angle
Image		
Video Compression		H.265 / H.264 / MJPEG
H.265 Compression Standard		Main Profile @Leve4.1 High Tier
Resolution		5MP (2592 × 1944), 4MP (2560 × 1440), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
Main Stream		60Hz : 4MP (1 ~ 30fps) / 2K (1 ~ 30fps) / 3MP (1 ~ 30fps) / 1080P (1 ~ 30fps) / 720P (1 ~ 30fps) 50Hz : 4MP (1 ~ 25fps) / 2K (1 ~ 25fps) / 3MP (1 ~ 25fps) / 1080P (1 ~ 25fps) / 720P (1 ~ 25fps)
Bit Rate		128 Kbps ~ 10 Mbps
Encode Mode		VBR / CBR
Quality		Five levels under VBR; Freely adjustable under CBR
Image Settings		ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
Audio Compression		G711A / U
ROI		Each ROI to be configured separately
Interfaces		
Network		RJ45
Audio		MIC IN × 1, MIC OUT × 1
Video Output		CVBS video output (BNC × 1)
Storage Card		Support SD card, up to 128GB
RS485		Yes
Alarm Input		1 CH
Alarm Output		1 CH
Functions		
Remote Monitoring		IE browsing, CMS remote control
Online Connection		Support simultaneous monitoring for up to 6 users; Support multi-stream real time transmission
Network Protocol		TCP / IP, UDP, DHCP, UPnP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol		ONVIF, GB-T/28181-2011
Storage		SD card local storage, network remote storage
Smart Alarm		Motion alarm, sensor alarm
PTZ		RS485 × 1
IR Distance		70 ~ 100 m
Water-proof		IP66
Others		
Power Supply		DC12V(PoE power supply optional)
Power Consumption		< 16W
Operating Environment		- 20 °C ~ 50 °C, 10 % ~ 90 % relative humidity
Dimensions (mm)		Φ 109 × 360
Weight (net)		1700g
Installation		Wall mounting, ceiling mounting